



vdo-instruments.com

# VDO Reed Switch Fuel Senders

Rugged construction ensures long life in extreme conditions

These rugged fuel senders are designed to be used in a variety of marine and industrial applications. Stainless steel tubes makes them ideal for various fluid measuring. Non-corrosion mounting flanges are ideally suited to marine and weather exposed environments. Ensuring long life in extreme conditions.

## Features

- Suitable for fuel and water measuring applications
- Design minimizes slosh related gauge dithering
- Compatible with fuel/water gauges from various manufacturer's

## Technical Specifications

- 304 stainless steel measuring tube construction
- Protection Class IP 67
- Standard SAE 5 hole mounting flange with gasket
- Standard lengths from 150mm up to 900mm (6in to 36in)
- 240-33 Ohm and 0-90 Ohm resistance available, with 10-180 Ohm and 0-5V planned Q3/Q4 2020)

# VDO

## Reed Switch Fuel Senders

vdo-instruments.com

### 240-33Ω Reed Switch Fuel Sender



VDO Part Number	Sender Length	Connector
226-615	150 mm	.250" Insulated Spade
226-618	180 mm	.250" Insulated Spade
226-620	200 mm	.250" Insulated Spade
226-623	230 mm	.250" Insulated Spade
226-625	250 mm	.250" Insulated Spade
226-627	270 mm	.250" Insulated Spade
226-630	300 mm	.250" Insulated Spade
226-633	330 mm	.250" Insulated Spade
226-635	350 mm	.250" Insulated Spade
226-640	400 mm	.250" Insulated Spade
226-645	450 mm	.250" Insulated Spade
226-660	600 mm	.250" Insulated Spade
226-666	660 mm	.250" Insulated Spade
226-680	800 mm	.250" Insulated Spade
226-690	900mm	.250" Insulated Spade

### 0-90Ω Reed Switch Fuel Sender

Replacement for:  
0-90 Ohm Tube Type Senders



VDO Part Number	Sender Length	Connector	Replaces Tube Type Single Pack
2910002233700	150 mm	Unterminated Wires	224-215
2910002233800	200 mm	Unterminated Wires	224-220
2910002233900	250 mm	Unterminated Wires	224-225
2910002234000	300 mm	Unterminated Wires	224-230
2910002234100	350 mm	Unterminated Wires	224-235
2910002234200	400 mm	Unterminated Wires	224-240
2910002234300	450 mm	Unterminated Wires	224-245
2910002234400	500 mm	Unterminated Wires	224-250
2910002234500	550 mm	Unterminated Wires	224-255
2910002234600	600 mm	Unterminated Wires	224-260
2910002234700	650 mm	Unterminated Wires	224-265
2910002234800	700 mm	Unterminated Wires	224-270
2910002234900	750 mm	Unterminated Wires	224-275
2910002235000	800 mm	Unterminated Wires	224-280